

RL LED

Roadway RL60 Series

- Designed for roadway, parking, area and perimeter lighting; These versatile Roadway luminaires replace existing cobra-head style fixtures from 200-400w while saving up to 65% in energy; LED luminaires feature optimum uniformity, elimination of 'hot spots' and zero uplight
- 12000 lumens at 700 mA
- Standard IES distributions of Type II, III, IV, V with up to 86 LPW efficiency
- Two 30 LED light engines
- 120-277V, 347/480V electronic dimming drivers (4) standard
- Die-cast aluminum housing
- Lektrocote® finish in 2 standard and custom colors
- IP65 LED light engine assembly and drivers
- 10KA surge protector standard



ROADWAY

ORDERING INFORMATION

SERIES	NUMBER OF LEDS	VOLTAGE	CCT	IES DISTRIBUTION	DRIVE CURRENT	PHOTOCONTROL RECEPTACLE	OPTIONS	FINISH
RL Zero uplight large Roadway	60L 60 LEDs	U 120-277V 5 480V F 347V	3K 3000K nominal, 80 CRI 4K 4200K nominal, 70 CRI 5K 5100K nominal, 67 CRI	2 Type II 3 Type III 4 Type IV 5M Type V	BLANK 700 mA (141w)	2 None 3 Yes	F(X) Fusing, replace X with voltage, specify: 1-120V 2-208V 3-240V 4-277V 5-480V 6-347V BC² Back-light Control	BK Black DB Dark Bronze CC¹ Custom Color (Reference RAL#) GR Gray PS Platinum Silver WH White

1 Contact factory for minimum order quantities
2 Recommended for Type III and IV distributions only

PERFORMANCE INFORMATION

Series Number	Equivalency		Delivered Lumens		Number of LEDs	System Watts		Lumens Per Watt	CCT	Drivers/Current
	MH	HPS	Type 2	Type 3		120V-277V	347V-480V			
RL-60LU-3K	250w	150w	8833	8694	60	141	141	63	3000K	4@700mA
RL-60LU-4K	320w	200w	11044	11062	60	141	141	79	4200K	4@700mA
RL-60LU-5K	320w	250w	11759	12058	60	141	141	85	5100K	4@700mA

DIMENSIONS



A	B	C	EPA	Weight
8.25"	15.75"	36.75"	1.0 ft. ²	28 lbs.
210 mm	400 mm	933 mm	0.1 m ²	12.7 kg.



HUBBELL
Outdoor Lighting